



DON 480 BALING TWINE

DON 480 is one of the signature Twines of the Donaghy's range and has been a favorite over many years for the tougher jobs in general purpose Large Square Baling.

DON 480 encompasses both strength & longer running length per spool, which makes it a great all rounder in the Large Square Bale Twine market.



APPLICATION	IP CODE	DESCRIPTION	COLOUR	PACKS PER PALLET	APPROX BALES PER PACK 5 STRING	APPROX BALES PER PACK 6 STRING
BIG SQUARE BALERS	TWN0008	DON 480 BIG SQUARE 2 X 1,220M PACK	ORANGE	24	73	61

USAGE AND APPLICATION

Designed for the tough baling environment of Australia, DON 480's combination of strength and longer running length makes it an ideal general purpose LSB twine for use in all modern conventional Large Square balers.

DON 480 is designed for both the Contractor and Farmer/End-user for use in crops types such as; Pasture, Cereal, Straw & Silage and will save on baler wear & tear plus down time re-loading.

FEATURES AND BENEFITS

- Good Knot holding capabilities
- Smooth run through baler, reducing wear on Knotter equipment
- Extra Length spools, resulting in extra bales pressed per spool
- Less packs twine required per load for more bales pressed
- Designed for Australian conditions with 12 Month guarantee against UV degradation
- Average Runnage of 132m/kg

FAQ'S

- Is DON 480 Big Square suitable for baling Cereal & Pasture Hay & Silage?

Yes, it is suitable for baling all cereal & Pasture hay's and Silage in all Conventional Large Square Balers.

- Is DON 480 Big Square suitable for baling Straw?

Yes, it is suitable for baling straw in all Conventional Large Square Balers.

- Will I have to adjust my knotter's in the baler if I change my twine?

There may be a need to adjust the knotter settings if using different thickness (Tex) of twine.

FAQ'S

- Is the colour of the Twine important?

The addition of coloured master batch can change the characteristics of the polymers. However, all colours from the Integrated Packaging Twine range are suitable for baling in Australian conditions. Some colours are preferred by consumers more than others due to visual requirements such as visibility in certain crop types, night baling or end-users requirements.

- Do I need to run a higher strength twine on the outside Knotters of my Baler?

This is an option to reduce the need for higher strength twine across the whole Knotters, but can depend on crop type and conditions of crop being baled.

- Are the thicker, stronger Twines more abrasive on my knotter mechanism?

Twines that are thicker are often harsher and cause wear on both twine guides & Knotter parts.

- Is DON 480 suitable for Large Square High Density Balers?

DON 480 has been designed for baling in standard LSB balers. IP have other high performance twines available for High Density baling.