



GREAT WHITE SILAGE WRAP

Great White Silage Film is the latest in Silage Film technology based on a 5 layer construction, giving superior puncture & tear properties.

Great White Silage Film is designed for the Australian Silage market giving even stretch properties with reduced windowing, along with outstanding cling levels to make excellent anaerobic conditions for ensiling fodder. Able to be stretched up to 60%, Great White is a new generation of Silage Film designed to give maximum performance and returns.



APPLICATION	ROLLS PER PALLET	COLOUR	ORDER CODE	APPROX BALES PER ROLL
BIG ROUND BALERS	40	GREEN	SIL0037	27

USAGE AND APPLICATION

Silage wrap is suitable for creating anaerobic conditions with Silage. Used for wrapping round and square bales on individual turntable wrappers, high speed satellite wrappers and tubeline wrappers.

Individual Round Bales: apply a minimum of 4 layers with 50% overlap.

Individual Square Bales: apply a minimum of 6 layers with 50% overlap.

Tubeline round and square bales: apply a minimum of 6 layers.

To extend film life beyond 12 months apply additional layers.

Recommend pre-stretch ratio of maximum 60%.

FEATURES AND BENEFITS

- 5 Layer Film giving superior puncture & tear resistance
- Superior oxygen barrier properties enhancing the fermentation process
- Designed for general Silage wrapping on High Speed Wrapping Machines
- Manufactured from Quality resins with high tack levels for superior performance
- Designed for Australian conditions with 12 Month guarantee against UV degradation.

FAQ'S

- Can I wrap both Square & Round bales with Great White Silage Film?

Yes, Great White is suitable for both Square & Round bale wrapping.

FAQ'S

- Is Great White suitable to use on a Tubeline or High Speed wrapping machine?

Yes, Great White can be used on all makes and models of Tubeline & high Speed Wrapping machines.

- How many layers of film do I need to achieve an air-tight (anaerobic) bale?

Four (4) layers of film are required to achieve an acceptable anaerobic (air tight) state for silage to ensile.

- How many wraps should I do for a round bale?

Rule of thumb: Wrap the bale completely once at 50% film overlap, counting the wraps (revolutions), then double and add one more revolution which will give the required minimum four (4) layers of film.

- How many layers should I have on an Tubeline wrapped bale?

A minimum of six (6) layers are required on Tubeline wrapping to support film strength where bales join each other.

- How long can I expect my Silage Film to last?

Integrated Packaging Silage film is guaranteed for 12 months against UV degradation

- Is there any difference to the quality of Silage using different colours?

As long as bales are wrapped with the recommended wraps to achieve anaerobic conditions for ensiling, green, black or white Silage films are suitable.

- What can I do to help store my wrapped bale silage for longer?

Using six (6) + layers of film is suggested for storing wrapped baled silage for longer periods.

- What can I do to help the storage process of my Silage bales?

Start with a well cleared site for stacking. Placing Rodent bait stations around the perimeter of the Silage bale stack will help prevent attack by Rats & Mice.