



SILAWRAP PLUS

SilaWRAP Plus is a premium quality silage wrapping film combining the latest advances in patented pre-stretch technology to help achieve greater wrapping efficiencies. Up to 50% more bales wrapped out of every roll of film, saving down time and increasing wrapping efficiencies.



APPLICATION	IP CODE	DESCRIPTION	COLOUR	PALLET QTY.	APPROX. NO. BALES PER ROLL
ROUND & SQUARE BALE SILAGE	SIL0015	SILAWRAP PLUS 730MM X 2,300M X 16µm	GREEN	40	42
ROUND & SQUARE BALE SILAGE	SIL0017	SILAWRAP PLUS 730MM X 2,300M X 16µm	WHITE	40	42
ROUND & SQUARE BALE SILAGE	SIL0018	SILAWRAP PLUS 730MM X 2,300M X 16µm	BLACK	40	42

*APPROX. NO. BALES PER ROLL BASED ON A 1.2M X 1.2M ROUND BALE WITH 4 LAYERS AT 55% STRETCH.

USAGE AND APPLICATION

Silage wrap suitable for creating anaerobic conditions with Silage. Used for wrapping round and square bales on individual turntable wrappers, high speed satellite wrappers and tubeline wrappers.

Individual Round Bales: apply a minimum of 4 layers with 50% overlap.

Individual Square Bales: apply a minimum of 6 layers with 50% overlap.

Tubeline round and square bales: apply a minimum of 6 layers

To extend film life beyond 12 months apply additional layers. Recommend pre-stretch ratio of maximum 55%.

FEATURES AND BENEFITS

- A Premium quality silage wrapping film
- Yields up to 50% more bales per roll
- Environmentally friendly with less Disposal
- Cost and production efficiencies
- Superior oxygen barrier properties enhancing the fermentation process.
- Designed for general Silage wrapping
- Manufactured from Quality resins for high puncture and tear resistance
- Designed for Australian conditions with 12 Month guarantee against UV degradation
- Made in Australia to International Quality Standards

FAQ'S

- Can I wrap both Square & Round bales with SilaWRAP Plus?

SilaWRAP Plus is suitable for Round bale wrapping, however, wrapping Large Square bales of Silage may require a heavier grade of film to handle the aggressive corners on Square bales.

FAQ'S

- Is SilaWRAP Plus suitable to use on a Tubeline wrapping machine?

SilaWRAP Plus can be used on all makes & models of Tubeline Wrapping machines.

- How many layers of film do I need to achieve an airtight (anaerobic) bale?

Four (4) layers of film are required to achieve an acceptable anaerobic (air tight) state for silage to ensile.

- How many wraps should I do for a round bale?

Rule of thumb: Wrap the bale completely once at 50% film overlap, counting the wraps (revolutions), then double and add one more revolution which will give the required minimum 4 layers of film.

- How many layers should I have on an Tubeline wrapped bale?

A minimum of Six (6) layers are required on Tubeline wrapping to support film strength where bales join each other.

- How long can I expect my Silage Film to last?

Integrated Packaging Silage film is guaranteed for 12 months against UV degradation with a 55% stretch ratio.

- Is there any difference to the quality of Silage using different colours?

As long as bales are wrapped with the recommended wraps to achieve anaerobic conditions for ensiling, green, black or white Silage films are suitable.

- What can I do to help store my wrapped bale silage for longer?

Using 6 + layers of film is suggested for storing wrapped baled silage for longer periods.

- What can I do to help the storage process of my Silage bales?

- Start with a well cleared site for stacking. Placing Rodent bait stations around the perimeter of the Silage bale stack will help prevent attack by Rats & mice.